

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

1.1. Product identifier

Trade name PE-100 Part A CARMEL / TOFFEE
Product no. PE-100A TFFE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture None known.
Restricted to professional and industrial use.
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company and address **APN Performance Coatings**
3321 County Rd A
54901 Oshkosh, WI
United States
+1(920)-231-0850
<https://www.apnonweiler.com/>
Contact person Jason Brennan
E-mail SDS@apnonweiler.com
SDS date 6/18/2026
SDS Version 1.0

1.4. Emergency telephone number

INFOTRAC: 24 Hour Emergency: 1-800-535-5053. Outside U.S. and Canada: 1-352-323-3500. INFOTRAC Customer ID: 72826.

SECTION 2: HAZARD(S) IDENTIFICATION

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.
Skin Sens. 1; H317, May cause an allergic skin reaction.
Eye Irrit. 2; H319, Causes serious eye irritation.
Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Warning

Hazard statement(s)

Causes skin irritation. (H315)
May cause an allergic skin reaction. (H317)
Causes serious eye irritation. (H319)
Toxic to aquatic life with long lasting effects. (H411)

Precautionary statement(s)

General

Not applicable.

Prevention

Avoid breathing mist/vapour. (P261)
Wash hands thoroughly after handling. (P264)
Contaminated work clothing should not be allowed out of the workplace. (P272)

Response	Avoid release to the environment. (P273) Wear eye protection/protective gloves/protective clothing. (P280) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338) If skin irritation or rash occurs: Get medical advice/attention. (P333+P313) If eye irritation persists: Get medical advice/attention. (P337+P313) Take off contaminated clothing and wash it before reuse. (P362+P364) Collect spillage. (P391)
Storage	Not applicable.
Disposal	Dispose of contents/container in accordance with local regulation. (P501)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
reaction product: bisphenol-A-(epichlorhydrin);epoxy resin (number average molecular weight ≤ 700)	CAS No.: 25068-38-6	80-95%	Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Aquatic Chronic 2, H411	
1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	CAS No.: 17557-23-2	3-5%	Skin Irrit. 2, H315 Skin Sens. 1, H317	

Where the concentration of an ingredient is expressed as a range the exact concentration has been withheld as a trade secret.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

SECTION 4: FIRST-AID MEASURES

4.1. Description of first aid measures

General information	If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.
Inhalation	Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.
Skin contact	IF ON SKIN: Wash with plenty of water and soap. Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.
Eye contact	If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person.
Never give the person anything to drink.
In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.
Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material Always store in containers of the same material as the original container.

Storage conditions No specific requirements.

Incompatible materials Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

Long term exposure limit (ACGIH TLV) (mg/m^3): 10

Long term exposure limit (NIOSH REL) (mg/m^3): Potential occupational carcinogen; (ultrafine particles) / 2.4 (fine) / 0.3 (ultrafine)

m-xylene;xylene;o-xylene;p-xylene

Short term exposure limit (STEL) (ACGIH TLV) (ppm): 150

Short term exposure limit (STEL) (NIOSH REL) (ppm): 150

Long term exposure limit (OSHA Table Z-1) (mg/m^3): 435

Long term exposure limit (OSHA Table Z-1) (ppm): 100

Long term exposure limit (ACGIH TLV) (ppm): 100

Carbon black

Long term exposure limit (OSHA Table Z-1) (mg/m^3): 3.5

Long term exposure limit (ACGIH TLV) (mg/m^3): 3 (Inhalable)

Long term exposure limit (NIOSH REL) (mg/m^3): 3.5 (without PAHs); when PAHs are present, NIOSH considers carbon black to be a potential occupational carcinogen.

No substances are listed with a permissible exposure limit CIB 66 [NIOSH 2014-100]

Part 1910 - Occupational Safety and Health Standards (29 CFR 1910.1000 TABLE Z-1 - Limits for Air Contaminants)

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios There are no exposure scenarios implemented for this product.

Exposure limits Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally No specific requirements.

Respiratory Equipment
No specific requirements.

Skin protection

No specific requirements.

Hand protection

No specific requirements.

Eye protection

No specific requirements.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	Toffee
Odor	Mild
Odor threshold (ppm)	No data available
pH	No data available
Density (g/cm ³)	1.19
Kinematic viscosity	No data available.
Dynamic viscosity	4,000 centiPoise
Particle characteristics	Not applicable - product is a liquid

Phase changes

Melting point/freezing point (°F)	No data available
Softening point/range (°F)	Does not apply to liquids.
Boiling point (°F)	No data available
Vapor pressure	No data available
Relative vapor density	No data available
Decomposition temperature (°F)	No data available

Data on fire and explosion hazards

Flash point (°F)	No data available
Flammability (°F)	No data available
Auto-ignition temperature (°F)	No data available
Explosion limits (% v/v)	No data available

Solubility

Solubility in water	No data available
n-octanol/water coefficient (LogKow)	No data available
Solubility in fat (g/L)	No data available

9.2. Other information

Evaporation rate (n-butylacetate = 100)	No data available
Other physical and chemical parameters	No data available.
Oxidizing properties	No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions, including those associated with foreseeable emergencies

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.
Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Other information

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] has been classified by IARC as a group 2B.
m-xylene;xylene;o-xylene;p-xylene has been classified by IARC as a group 3.
Carbon black has been classified by IARC as a group 2B.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Based on available data, the classification criteria are not met.

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)

m-xylene;xylene;o-xylene;p-xylene is listed with EPA Hazardous Waste Number: U239

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
DOT	-	-	-	-	-	-
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Transport hazard class: 9 Label: 9 Classification code: M6 	III	Yes	Limited quantities: 5 L EmS: F-A S-F See below for additional information.
IATA	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Transport hazard class: 9 Label: 9 Classification code: M6 	III	Yes	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

These substances when carried in single or combination packaging's containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of DOT/IMDG/IATA provided the packaging's meet the general specifications for packaging: Part 178 (DOT) / 4.1.1.1, 4.1.1.2, 4.1.1.4 - 4.1.1.8 (IMDG) / 5.0.2.4.1, 5.0.2.6.1.1, 5.0.2.8 (IATA).

-
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. U.S. Federal regulations

TSCA (the non-confidential portion)	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] is listed m-xylene;xylene;o-xylene;p-xylene is listed Carbon black is listed
Clean Air Act	m-xylene;xylene;o-xylene;p-xylene is regulated as a hazardous air pollutant (HAPS)
EPCRA Section 302	None of the components are listed
EPCRA Section 304	None of the components are listed
EPCRA section 313	m-xylene;xylene;o-xylene;p-xylene is listed
CERCLA	m-xylene;xylene;o-xylene;p-xylene is regulated with a Reportable Quantity (RQ) of: 100 pounds
Hazardous chemical inventory reporting	

15.3. State regulations

California / Prop. 65	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] is known to cause: Cancer NSRL/MADL ($\mu\text{g/day}$): 440 NSRL (unbound, airborne particles with diameters of $\leq 10 \mu\text{m}$); 44 NSRL (unbound, airborne particles with diameters of $\leq 0,8 \mu\text{m}$) — Carbon black is known to cause: Cancer —
Massachusetts / Right To Know Act	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] is listed m-xylene;xylene;o-xylene;p-xylene is listed Carbon black is listed
New Jersey / Right To Know Act	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] / Substance number: 1861 — m-xylene;xylene;o-xylene;p-xylene / Substance number: 2014 m-xylene;xylene;o-xylene;p-xylene is on the Special Health Hazard Substance List — Carbon black / Substance number: 0342

New York / Right To Know Act

Carbon black is on the Special Health Hazard Substance List

—
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] is listed
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] is regulated with a Threshold Reporting Quantity (TRQ) of: 100 pounds

—
m-xylene;xylene;o-xylene;p-xylene is listed
m-xylene;xylene;o-xylene;p-xylene is regulated with a Reportable Quantity (RQ) of: 1000 pounds
m-xylene;xylene;o-xylene;p-xylene is regulated with a Threshold Reporting Quantity (TRQ) of: 0 pounds

Pennsylvania / Right To Know Act

—
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] is listed

—
m-xylene;xylene;o-xylene;p-xylene is listed
m-xylene;xylene;o-xylene;p-xylene is hazardous to the environment (E)

—
Carbon black is listed

15.4. Restrictions for application

Restricted to professional users.

15.5. Demands for specific education

No specific requirements.

15.6. Additional information

Not applicable.

15.7. Chemical safety assessment

No

15.8. Sources

OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H319, Causes serious eye irritation.
H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CERCLA = Comprehensive Environmental Response Compensation and Liability Act

DOT = Department of Transportation

EINECS = European Inventory of Existing Commercial chemical Substances

EPCRA = Emergency Planning and Community Right-To-Know Act

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HCIS = Hazardous Chemical Information System

HNOC = Hazards Not Otherwise Classified

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogKow = logarithm of the n-octanol/water coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NFPA = National Fire Protection Association

NIOSH = National Institute for Occupational Safety and Health

OECD = Organisation for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

PBT = Persistent, Bioaccumulative and Toxic

RCRA = Resource Conservation and Recovery Act

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SARA = Superfund Amendments and Reauthorization Act

SCL = A specific concentration limit.

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by HCS (29 CFR 1910.1200).

The safety data sheet is validated by

Hermann Wentz

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en