

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

1.1. Product identifier

Trade name	PP-S85 Part B
Product no.	PP-S85B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture	None known. Restricted to professional and industrial use.
Uses advised against	Paint

1.3. Details of the supplier of the safety data sheet

Company and address	APN Performance Coatings 4400 A. Chomedey O H7R 6E9 Laval, QC Canada +1(450)-818-0626 https://purepoxy.com
Contact person	Mickael Blais Roberge
E-mail	mblaisroberge@apnonweiler.com
SDS date	2026-06-19
SDS Version	1.0

1.4. Emergency telephone number

24-Hour Emergency Telephone Number Canada (CANUTEC): (613) 996-6666

SECTION 2: HAZARD(S) IDENTIFICATION

Classified as hazardous according to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272).

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.
Skin Irrit. 2; H315, Causes skin irritation.
Skin Sens. 1; H317, May cause an allergic skin reaction.
Eye Irrit. 2; H319, Causes serious eye irritation.
Muta. 1B; H340, May cause genetic defects.
Carc. 1B; H350, May cause cancer.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Flammable liquid and vapour. (H226)
Causes skin irritation. (H315)
May cause an allergic skin reaction. (H317)
Causes serious eye irritation. (H319)
May cause genetic defects. (H340)
May cause cancer. (H350)

Precautionary statement(s)

General

Not applicable.

Prevention

Obtain special instructions before use. (P201)

Response

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
 Avoid breathing mist/vapour. (P261)
 Wash hands thoroughly after handling. (P264)
 Contaminated work clothing should not be allowed out of the workplace. (P272)
 Wear protective gloves/protective clothing/eye protection/face protection. (P280)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
 IF exposed or concerned: Get medical advice/attention. (P308+P313)
 If skin irritation or rash occurs: Get medical advice/attention. (P333+P313)
 If eye irritation persists: Get medical advice/attention. (P337+P313)
 Take off contaminated clothing and wash it before reuse. (P362+P364)
 In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)

Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

Disposal

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances

Hexamethylene diisocyanate, oligomers
 Solvent naphtha (petroleum), light arom.;Low boiling point naphtha - unspecified
 Cumene
 hexamethylene-di-isocyanate

Additional labelling

Restricted to professional users.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS
3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Chemical name	Common name/synonyms	Identifiers	% w/w	Classification	Note
Hexamethylene diisocyanate, oligomers		CAS No.: 28182-81-2	60-80%	Skin Sens. 1, H317	
Solvent naphtha (petroleum), light arom.;Low boiling point naphtha - unspecified		CAS No.: 64742-95-6	15-25%	Asp. Tox. 1, H304 Muta. 1B, H340 Carc. 1B, H350	[19]
1,2,4-trimethylbenzene		CAS No.: 95-63-6	10-15%	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 Aquatic Chronic 2, H411	
Cumene		CAS No.: 98-82-8	<1%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 Carc. 1B, H350 Aquatic Chronic 2, H411	
hexamethylene-di-isocyanate		CAS No.: 822-06-0	<0.25%	Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.50 %) Eye Irrit. 2, H319 Acute Tox. 3, H331 Resp. Sens. 1, H334	

				(SCL: 0.50 %) STOT SE 3, H335	
--	--	--	--	----------------------------------	--

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST-AID MEASURES

4.1. Description of first aid measures

General information

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO_x)

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact a poison centre in order to obtain further advice. See section 1 "Emergency telephone number".

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof electrical/lighting/ventilating equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Store locked up. A sign warning of toxic materials shall be affixed to the room and cupboard containing the product(s).

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material Always store in containers of the same material as the original container.

Storage conditions No specific requirements.

Incompatible materials Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

ALBERTA

Cumene

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m³): 246

m-xylene;xylene;o-xylene;p-xylene

Long term exposure limit (8 hours) (ppm): 100

Long term exposure limit (8 hours) (mg/m³): 434

Short term exposure limit (15 minutes) (ppm): 150

Short term exposure limit (15 minutes) (mg/m³): 651

ethylbenzene

Long term exposure limit (8 hours) (ppm): 100

Long term exposure limit (8 hours) (mg/m³): 434

Short term exposure limit (15 minutes) (ppm): 125

Short term exposure limit (15 minutes) (mg/m³): 543

hexamethylene-di-isocyanate

Long term exposure limit (8 hours) (ppm): 0.005

Long term exposure limit (8 hours) (mg/m³): 0.03

Occupational Health and Safety Code 2009 Order, Alta Reg 87/2009 (revised in 2018)

BRITISH COLUMBIA

Cumene

Time-Weighted Average Limit (TWA): 25 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 75 ppm

m-xylene;xylene;o-xylene;p-xylene

Time-Weighted Average Limit (TWA): 100 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 150 ppm

ethylbenzene

Time-Weighted Average Limit (TWA): 20 ppm

hexamethylene-di-isocyanate

Time-Weighted Average Limit (TWA): 0.005 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): C 0.01 ppm

Annotations:

S(R) = The substance has the potential to produce sensitization by respiratory route.

OHS Regulation Part 5: Chemical Agents and Biological Agents.

ONTARIO

Cumene

Time-Weighted Average Limit (TWA): 50 ppm

m-xylene;xylene;o-xylene;p-xylene

Time-Weighted Average Limit (TWA): 100 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 150 ppm

ethylbenzene

Time-Weighted Average Limit (TWA): 20 ppm

hexamethylene-di-isocyanate

Time-Weighted Average Limit (TWA): 0.005 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): C 0.02 ppm

Regulation 833 (Control of Exposure to Biological or Chemical Agents) and Ontario Regulation 490/09 (Designated Substances)

QUEBEC

Cumene

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m³): 246

m-xylene;xylene;o-xylene;p-xylene

Long term exposure limit (8 hours) (ppm): 100

Long term exposure limit (8 hours) (mg/m³): 434

ethylbenzene

Long term exposure limit (8 hours) (ppm): 20

Annotations:

Note 3 = Where the use of these products is permitted.

hexamethylene-di-isocyanate

Long term exposure limit (8 hours) (ppm): 0.005

Long term exposure limit (8 hours) (mg/m³): 0.034

Annotations:

EM = Exposure must be reduced to a minimum in accordance with section 42.

S = Sensitizer.

Regulation respecting occupational health and safety (Chapter S-2.1, r. 13)

SASKATCHEWAN

Cumene

Long term exposure limit (8 hours) (ppm): 50

Short term exposure limit (15 minutes) (ppm): 74

m-xylene;xylene;o-xylene;p-xylene

Long term exposure limit (8 hours) (ppm): 100

Short term exposure limit (15 minutes) (ppm): 150

ethylbenzene

Long term exposure limit (8 hours) (ppm): 100

Short term exposure limit (15 minutes) (ppm): 125

Annotations:

T20 = Substance is also included in Table 20 of The Occupational Health and Safety Regulations and subject to Sections 306 and 311

hexamethylene-di-isocyanate

Long term exposure limit (8 hours) (ppm): 0.005

Short term exposure limit (15 minutes) (ppm): 0.015

The Occupational Health and Safety Regulations, 2020, Chapter S15.1 Reg 10.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Do not recirculate outlet air that contain the substances.

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only protective equipment with a recognized certification mark, e.g. the UL mark.

Respiratory Equipment

Type	Class	Colour	Standards	
Respiratory protection is not needed in the event of adequate ventilation.				
Combination filter A2P2	Class 2	Brown/White	EN14387	

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
4H	0,068 - 0,084	> 480	EN374-2, EN16523-1, EN388	

Eye protection

Type	Standards	
Safety glasses with side shields.	EN ISO 16321-1	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	Clear
Odour	Aromatic
Odour threshold (ppm)	No data available
pH	No data available
Density (g/cm ³)	-
Relative density	1.065
Kinematic viscosity	No data available
Dynamic viscosity	60 centiPoise
Particle characteristics	Not applicable - product is a liquid

Phase changes

Melting point/Freezing point (°C)	No data available
Softening point/range (°F)	Does not apply to liquids.
Boiling point (°C)	No data available
Vapour pressure	No data available
Relative vapour density	No data available
Decomposition temperature (°C)	No data available

Data on fire and explosion hazards

Flash point (°C)	No data available
Flammability (°C)	The material is ignitable.
Auto-ignition temperature (°C)	No data available
Explosion limits (% v/v)	No data available

Solubility

Solubility in water	No data available
n-octanol/water coefficient (LogKow)	No data available
Solubility in fat (g/L)	No data available

9.2. Other information

Evaporation rate (n-butylacetate = 100) No data available

Other physical and chemical parameters No data available.

Oxidizing properties No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Carcinogenic effects: This product contains substances considered or proven to be carcinogenic. The carcinogenic effects may be triggered subsequent to exposure through inhalation, skin contact or ingestion.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.

Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Other information

Cumene has been classified by IARC as a group 2B.

m-xylene;xylene;o-xylene;p-xylene has been classified by IARC as a group 3.

ethylbenzene has been classified by IARC as a group 2B.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Cumene is listed with EPA Hazardous Waste Number: U055

m-xylene;xylene;o-xylene;p-xylene is listed with EPA Hazardous Waste Number: U239

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
TDG	UN1263	PAINT RELATED MATERIAL	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1263	PAINT RELATED MATERIAL	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1263	PAINT RELATED MATERIAL	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

TDG / See Schedule 1 for any information on special provisions, requirements, or warnings in connection with transport. See part 3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.2. Canadian lists**

NDSL

None of the components are listed

DSL

Hexamethylene diisocyanate, oligomers

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified
1,2,4-trimethylbenzene

Cumene

m-xylene; xylene; o-xylene; p-xylene

ethylbenzene

hexamethylene-di-isocyanate

15.4. Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

15.5. Demands for specific education

No specific requirements.

Additional information

Not applicable.

15.7. Chemical safety assessment

No

Sources

Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SECTION 16: OTHER INFORMATION**Full text of H-phrases as mentioned in section 3**

H226, Flammable liquid and vapour.

H304, May be fatal if swallowed and enters airways.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H331, Toxic if inhaled.

H332, Harmful if inhaled.

H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335, May cause respiratory irritation.

H340, May cause genetic defects.

H350, May cause cancer.

H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ANSI = American National Standards Institute
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
DSL = Domestic Substances List
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
HHNOC = Health Hazards Not Otherwise Classified
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
LogKow = logarithm of the n-octanol/water coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NDSL = Non-domestic substances list
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PHNOC = Physical Hazards Not Otherwise Classified
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
SCL = A specific concentration limit.
SOR = Statutory Orders and Regulations
STEL = Short-term exposure limits
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TDG = Transportation of Dangerous Goods
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative
WHIMS = Workplace Hazardous Materials Information System

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by WHMIS 2022

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Hermann Wentz

SDS date

2026-06-19

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: CA-en