

2 DAY SOLID COLOR SYSTEM

- Clean professional aesthetic ideal for commercial spaces
- Impact and abrasion resistant
- Cost effective solution
 - Outstanding value while still delivering a professional grade coating
- Available in a wide range of colors for customization and a polished appearance
 - Optional second topcoat: Nanoshield (high gloss), P-AU100 (satin)



2 Day Solid Color System

Basecoat - tinted	Body coat - tinted	Optional Topcoat
PurEpoxy PE-100 10-12 mils WFT 160-134 sq.ft./ga	PurEpoxy PE-100 16-20 mils WFT 100-80 sq.ft./ga	2-4 mils WFT 800-400 sq.ft./ga
Optional second topcoat : - Nanoshield (high gloss) 2-4 mils WFT, 800-400 sq.ft./ga - PE-AU100 (satin) 3-4 mils WFT, 530-400 sq.ft./ga		

3

OPTIONAL TOPCOAT

- Nanoshield or PE-AU100

2

BODY COAT – Solid Color

- PE-100 tinted - good hide

1

BASECOAT– PurEpoxy PE-100 (tinted)

- Provides a robust, long-lasting base for residential and commercial projects

CONCRETE SUBSTRATE

- Achieving optimal adhesion requires a clean, mechanically prepared substrate. Substrate must have a minimum Concrete Surface Profile (CSP) of 2 to 4. Crack Fillers (menders) provide fast, reliable filling for cracks, ensuring a smooth substrate.

* Concrete repair products include: PP-CF, PE-CF Fast, PE-CF Standard, PUR-CRR, PUR-CRE, and PUR-CRS (Urethane).

** Moisture Vapor Barrier. For any concrete slab with moisture issues, see our PurEpoxy MVB or VRM products.

Contact your local representative for our complete portfolio of moisture mitigation and crack repair solutions.