

## 1 DAY POLYASPARTIC FLAKE SYSTEM

- Installation and return to service within 24 hours
- Full Polyaspartic system delivers resistance to impact, abrasion, hot tire pickup and harsh chemicals
- Polyaspartic topcoat provides UV stability and high gloss shine that enhances the decorative flake underneath
- This Polyaspartic system can be applied in a wider range of temperatures and humidity



### 1 Day Polyaspartic Flake System

| Basecoat                                                     | Topcoat                                                      |
|--------------------------------------------------------------|--------------------------------------------------------------|
| <b>PurEpoxy PP-S85</b><br>8-12 mils WFT<br>200-134 sq.ft./ga | <b>PurEpoxy PP-S85</b><br>8-12 mils WFT<br>200-134 sq.ft./ga |

3

### TOPCOAT – PurEpoxy PP-S85

- For rapid return to service with UV resistance

2

### DECORATIVE BROADCAST into BASECOAT– Flake

- Multi colored flakes offer a customizable and durable finish

1

### BASECOAT– PurEpoxy PP-S85 (Tinted)

- Provides fast cure and extended working time, allowing efficient application with minimal downtime

### CONCRETE SUBSTRATE

- Achieving optimal adhesion requires a clean, mechanically prepared substrate. Substrate must have a minimum Concrete Surface Profile (CSP) of 2 to 4. Crack Fillers (menders) provide fast, reliable filling for cracks, ensuring a smooth substrate.

\* Concrete repair products include: PP-CF, PE-CF Fast, PE-CF Standard, PUR-CRR, PUR-CRE, and PUR-CRS (Urethane).

\*\* Moisture Vapor Barrier. For any concrete slab with moisture issues, see our PurEpoxy MVB or VRM products.

Contact your local representative for our complete portfolio of moisture mitigation and crack repair solutions.