

SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product Name: PUR-Guard™ Part C: TC
Revision Date: Jul 06, 2026
Version: 1.0
Manufacturer's Name: Res-Tek, Inc.
Address: 110 Riverside Drive SW Cartersville, GA, 30120 United States of America
Emergency Phone: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted).
Information Phone Number: 1-888-737-8351 / 1-770-427-4034
Product/Recommended Uses: Industrial Flooring Filler.

Date Printed: Jul 06, 2026
Supersedes Date: N.A.

SECTION 2) HAZARDS IDENTIFICATION

Classification

Serious Eye Damage - Category 1

Skin Irritation - Category 2

Skin Sensitizer - Category 1B

Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) - Category 3

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms



Signal Word

Danger

Hazardous Statements - Health

H318 - Causes serious eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H335 - May cause respiratory irritation

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P280 - Wear protective gloves, protective clothing, eye protection/face protection.

P264 - Wash thoroughly after handling.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P271 - Use only outdoors or in a well-ventilated area.

P233 - Keep container tightly closed.

Precautionary Statements - Response

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see First-Aid on this label).

P362 + P364 - Take off contaminated clothing. And wash it before reuse.

P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER/doctor if you feel unwell.

Precautionary Statements - Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements - Disposal

P501 - Dispose of contents/container in accordance with local/national/international regulations.

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0065997-15-1	PORTLAND CEMENT SILICATE	80% - 100%
0001305-78-8	CALCIUM OXIDE	0% - 1%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor. Take precautions to ensure your own safety (e.g. wear appropriate protective equipment).

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 30 minutes or until medical aid is available. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately call a POISON CENTER or doctor. Avoid direct contact. Wear chemical protective gloves, if necessary. Gently brush product off face. Do not rub eyes. Let the eyes water naturally for a few minutes. Look right and left, then up and down. Do not attempt to manually remove anything from the eyes.

Skin Contact

Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Rinse skin with lukewarm, gently flowing water/shower for a duration of 30 minutes or until medical aid is available. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before re-use or discard.

Ingestion

Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. If vomiting occurs naturally, lie on your side, in the recovery position.

Most important symptoms and effects, both acute and delayed

No data available.

Indication of any immediate medical attention and special treatment needed

Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small Fire : Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire : Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards Arising from the Chemical

Fire will produce irritating and corrosive gases.

Precautions for Firefighters

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Equipment

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Evacuate and isolate hazard area and keep unauthorized personnel away. Ventilate closed spaces before entering. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Protective Equipment

Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA).

Personal Precautions

Do not get on skin, eyes or clothing. Do not breathe dust.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material and water from clean-up/firefighting from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Avoid raising dust. Safely collect powdered material and deposit in sealed containers for disposal. Ventilate and wash area after clean-up is complete.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use. Do not get in eyes, on skin, or on clothing. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored. All containers must be properly labelled. Do not breathe dust.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

Storage Room Requirements

Store in a cool, dry, well ventilated area, away from sources of ignition and incompatibilities. Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Indoor storage should meet OSHA standards and appropriate fire codes. Empty containers retain residue and may be dangerous.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear Dust-proof goggles with side shields

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)
CALCIUM OXIDE	1			5				2
PORTLAND CEMENT SILICATE	[1]; [3];			[15]; [5 (a)]; [50 mppcf];				1 (E,R)
Chemical Name	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA Skin designation	CAN_ONsmg	CAN_ONtmg
CALCIUM OXIDE				URT irr				
PORTLAND CEMENT SILICATE			A4	Pulm func; resp symptoms; asthma	A4			
Chemical Name	CAN_ONsppm	CAN_ONtppm	CAN_QCVEMP ppm - CANADA_QUE BEC VALEUR D"EXPOSITIO N MOYENNE PONDÉRÉE_p pm	CAN_QCVEMP mg - CANADA_QUE BEC VALEUR D"EXPOSITIO N MOYENNE PONDÉRÉE_m g	CAN_QCVECD ppm - CANADA_QUE BEC VALEUR D"EXPOSITIO N DE COURTE DURÉE_ppm	CAN_QCVECD mg - CANADA_QUE BEC VALEUR D"EXPOSITIO N DE COURTE DURÉE_mg	CAN_ALtppm	CAN_ALtmg
CALCIUM OXIDE				2				
PORTLAND CEMENT SILICATE				[1]; [10];				10
Chemical Name	CAN_ALsmg	CAN_AL_Notation	CANtppm	CANtmg	CANsppm	CANsmg	CAN_AL_Carcinogen	CAN_ALsppm
CALCIUM OXIDE				2		4		
PORTLAND CEMENT SILICATE				10,5a				
Chemical Name	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen			
CALCIUM OXIDE	2							
PORTLAND CEMENT SILICATE	10,5a							

(R) - Respirable fraction, A2 - Suspected Human Carcinogen, A4 - Not Classifiable as a Human Carcinogen, func - Function, irr - Irritation, pulm - Pulmonary, resp - respiratory, URT - Upper respiratory tract

The information in this Section does not list non-hazardous components that might have relevant NIOSH TWA (mg/m3), NIOSH Carcinogen, CANtmg, CAN_AL_Carcinogen, CAN_QCVEMPmg - CANADA_QUEBEC VALEUR D'EXPOSITION MOYENNE PONDÉRÉE_mg, CAN_ALtmg, ACGIH Carcinogen, ACGIH TLV Basis, ACGIH Notations, CAN_ONtmg, OSHA Tables (Z1, Z2, Z3), OSHA Carcinogen, OSHA TWA (ppm), OSHA TWA (mg/m3), ACGIH TWA (mg/m3) regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Solid, powder.
Color.	Gray or White.
Odor	None.
Odor Threshold (ppm)	Not available.
pH (Value)	>11.5 (1% w:w).
Melting Point (°C) / Freezing Point (°C)	Not available.
Boiling point/boiling range (°C):	>1000°C (>1832°F).
Flash Point (°C)	Not flammable. Not combustible.

Evaporation Rate	Not applicable.
Flammability (solid, gas)	Non-combustible solid.
Explosive Limit Ranges	Not applicable.
Vapour pressure (mmHg)	Not applicable.
Vapour Density (Air=1)	Not applicable.
Density (g/ml)	2.3 to 3.1 (19.2 – 25.9 Lb./gal)
Specific Gravity	2.3 – 3.1.
Solubility (Water)	0.1 to 1%.
Solubility (Other)	Not available.
Partition Coefficient (n-Octanol/water)	Not applicable.
Auto Ignition Point (°C)	Not applicable.
Decomposition Temperature (°C)	Not available.
Dynamic Viscosity (cPs @ 25°C)	Not applicable.
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Other information	None.

SECTION 10) STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical Stability

Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions/Polymerization

Will not occur.

Conditions To Avoid

Avoid heat, sparks, flame and contact with incompatible materials

Incompatible Materials

Strong bases, acids, and oxidizing agents.

Hazardous Decomposition Products

Oxides of carbon.

SECTION 11) TOXICOLOGICAL INFORMATION

Acute Toxicity

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is >20 mg/l

The Acute Toxicity Estimate (ATE) for an inhalation (dust and mist) exposure to this mixture is >5 mg/l

Aspiration Hazard

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Respiratory/Skin Sensitization

May cause an allergic skin reaction

Reproductive Toxicity

Based on available data, the classification criteria are not met.

Serious Eye Damage/Irritation

Causes serious eye damage

Skin Corrosion/Irritation

Causes skin irritation

Specific Target Organ Toxicity - Repeated Exposure

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

May cause respiratory irritation

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

Chronic Exposure

Based on available data, the classification criteria are not met.

Potential Health Effects - Miscellaneous

Based on available data, the classification criteria are not met.

SECTION 12) ECOLOGICAL INFORMATION**Ecotoxicity**

Based on available data, the classification criteria are not met.

Persistence and Degradability

No data available.

Bioaccumulative Potential

No data available.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS**Waste Disposal**

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

SECTION 14) TRANSPORT INFORMATION

Display Order	U.S. DOT Information	IMDG Information	IATA Information
UN Number:	Not Regulated	Not Regulated	Not Regulated
UN proper shipping name:	N/A	N/A	N/A
Transport Hazard class(es)	Not Applicable	Not Applicable	Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable
Hazardous substance (RQ)	Not Applicable	Not Applicable	Not Applicable
Environmental hazards	No Data Available	No Data Available	No Data Available
Special precautions for user	No Data Available	No Data Available	No Data Available

Transport in bulk according to Annex II of MARPOL and the IBC code	No Data Available	No Data Available	No Data Available
--	-------------------	-------------------	-------------------

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0065997-15-1	PORTLAND CEMENT SILICATE	80% - 100%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA), PA_HAZ - Pennsylvania Hazardous Substance List, TSCA_UVCB - CHEMICAL SUBSTANCES OF UNKNOWN OR VARIABLE COMPOSITION, COMPLEX REACTION PRODUCTS AND BIOLOGICAL MATERIALS, NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), TSCA_CDR - TSCA - Chemical Data Reporting (CDR) Rule, MA_RightToKnow - Massachusetts Right to Know
0001305-78-8	CALCIUM OXIDE	0.10% - 1.00%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA), PA_HAZ - Pennsylvania Hazardous Substance List, Canada_ON_419, NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), NJ_RightToKnow_SpecialHealthHazard_SubList - New Jersey Right To Know Special Health Hazard Substance List, TSCA_CDR - TSCA - Chemical Data Reporting (CDR) Rule, MA_RightToKnow - Massachusetts Right to Know, TSCATS - TOXIC SUBSTANCES CONTROL ACT TEST SUBMISSIONS

The information in this Section does not list non-hazardous components that might have relevant CA_Prop65, Canada_ON_419, MA_RightToKnow - Massachusetts Right to Know, MA_RightToKnow_Carcinogens - Massachusetts Right to Know POSES A RISK OF CANCER IN HUMANS, MA_RightToKnow_Hazardous - Massachusetts Right to Know SUBSTANCES THAT HAVE A LOW LETHAL DOSE (LD50) OR ARE DESIGNATED CARCINOGENS, NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), NJ_RightToKnow_SpecialHealthHazard_SubList - New Jersey Right To Know Special Health Hazard Substance List, PA_HAZ - Pennsylvania Hazardous Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA), TSCA_CDR - TSCA - Chemical Data Reporting (CDR) Rule, TSCATS - TOXIC SUBSTANCES CONTROL ACT TEST SUBMISSIONS, DSL - Domestic Substance List regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.



WARNING: This product can expose you to chemicals including Crystalline silica, chemicals (trace metals), which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

SECTION 16) OTHER INFORMATION

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL - Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA - Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT - US Department of Transportation.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.